

MCR-80

CB MOBILE
RADIO

QCOM AUSTRALIA PTY LTD

07 3856 1513 | WWW.QUALITYCOMMS.COM

Q COM



FEATURES

- 80 Channel UHF CB
- 5 WATT Power
- Loud 3 Watt Internal Speaker
- External Speaker (optional)
- Controller Mic (Channel Selector)
- Bluetooth Dongle & Speaker Mic (optional)
- Rugged Di-Cast Aluminium Body
- Excellent Replacement Warranty
- Includes Mounting Bracket

MCR-80

CB MOBILE RADIO

TYPICAL APPLICATIONS




01

TRAFFIC
CONTROL &
MANAGEMENT



02

CONSTRUCTION
SITE ACCESS



03

PLANT, TRUCK
& GENERAL
LOGISTICS

QCOM AUSTRALIA PTY LTD

07 3856 1513 | WWW.QUALITYCOMMS.COM



SPECIFICATIONS

GENERAL

Modulation Mode	FM
Frequency Range	Australia/New Zealand UHF 80CB
Frequency Error	+300Hz
Working Voltage	13.8V
Dimensions (DxWxH)	5x5.25x1 (With Bracket)
Working Current	3A MAX
Operating Temperature	-10C -+50C

TRANSMITTER

Output Power	5W
Spurious Radiation	<-30dBm
Transmit SNR	>45
Modulation Limiting	<5KHz
Adjacent Channel Power	<-60dBc
Modulation Sensitivity	5-15mV
Audio Pre-emphasis	-3~-7@AF=500Hz 3-7@AF=2KHz

RECEIVER

Receive Sensitivity	<-120dBm@SINAD=12dB
Audio Maximum Output	3 Watt
Distortion	<5.0%
Receive SNR	>40
Adjacent Channel Selectivity	60dB
Audio Response	2~6@AF=500Hz -8~-3@AF=2KHZ

MCR-80

CB MOBILE RADIO