COMMCR-80RM REMOTE MOUNT CB MOBILE RADIO



QCOM AUSTRALIA PTY LTD 07 3856 1513 | WWW.QUALITYCOMMS.COM





FEATURES

80 Channel UHF CB
99 Channel UHF Commercial
Remote Mount
Full Controller Microphone
LCD Display
5 WATT Power
Loud 3 WATT Internal Speaker
External Speaker (Optional)
Rugged Di-Cast Aluminium Body
Excellent Replacement Warranty

APPLICATIONS

Construction Site Access
Agriculture
Plant, Truck & General Logistics
Traffic Control & Management

OCOM AUSTRALIA PTY LTD

07 3856 1513 | www.qualitycomms.com PO Box 29, GRANGE QLD 4051

COMMCR-80RM REMOTE MOUNT CB MOBILE RADIO

General	Specifications
Model	MCR-80RM
Modulation Mode	FM
Frequency CB	476 / 477MHz (5 WATT)
Frequency Commercial	450MHz - 520MHz (5 WATT)
Frequency Error	+300Hz
Supply Voltage	13.8V
Dimensions (W x L x H)	5 x 5.25 x 1 (With Bracket)
Working Current	3A MAX
Operating Tempreture	- 10C to + 50C

Transmitter	
Output Power	5W
Spurious Radiation	<-30dBm
Transmitter SNR	> 45
Modulation Limiting	< 5KHz
Adjacent Channel Power	< -60dBc
Modulation Sensitivity	5-15mV
Audio Pre-emphasis	3-7 @ AF = 2KHz

Receiver		
Receive Sensitivity	< -120dBm @ SINAD = 12dB	
Audio Maximum Output	3 Watt	
Distortion	< 5.0%	
Receive SNR	> 40	
Adjacent Channel Selectivity	2 ~ 6 @ AF = 500Hz	
Audio Response	-8 ~ -3 @ AF = 2KHz	

- All specifications are subject to change without notice due to continuous development
- Complies with Australia / New Zealand RF standards







